



SIGN PROFILE

MINIMUM DIMENSIONS				
A	B	C	D	E
2"	6"	4"	2"	3"

NOTES:

1. ON ALL STREETS WITH DESIGNATED OR POSTED SPEEDS OF 25 MPH OR LESS, INITIAL UPPER-CASE LETTERS SHALL BE 4 INCHES IN HEIGHT AND LOWER-CASE LETTERS 3 INCHES IN HEIGHT.
2. LETTER STYLES FOR STREET NAME AND SUFFIX SHALL BE 4-INCH SERIES 'B' FROM THE *STANDARD ALPHABETS FOR HIGHWAY SIGNS MANUAL*.
3. FLAT BLANKS FOR 4-INCH STREET NAME SIGNS SHALL BE A MINIMUM 0.08 INCH GAUGE WITH 6063 T5 OR 6063 T6 ALODINE COATED ALUMINUM SUBSTRATE.
5. THE MINIMUM LENGTH SHALL BE 24 INCHES AND THE MAXIMUM LENGTH SHALL BE 36 INCHES.
6. BOTH SIDES OF STREET NAME SIGNS SHALL BE GREEN (PUBLIC) OR BLUE (PRIVATE) *3M HIGH INTENSITY PRISMATIC (HIP)* REFLECTIVE SHEETING.
7. ALL LETTERS AND NUMBERS SHALL BE WHITE *3M HIGH INTENSITY PRISMATIC (HIP)* REFLECTIVE SHEETING.
8. MOUNTING HARDWARE: SEE DRAWING 523.



Public Works Standard Drawings

**STREET NAME SIGN WITH 4-INCH LETTERING
FOR 25 MPH OR LESS SPEED LIMITS**

SCALE NTS	
DATE JAN '23	REV.
ENGR. DW	DRAWN KAE
DRAWING NO. 521	