



**SIGN PROFILE**

MINIMUM DIMENSIONS				
A	B	C	D	E
2"	9"	6"	2"	4½"

**NOTES:**

1. ON ALL STREETS WITH DESIGNATED OR POSTED SPEEDS OF 30 MPH OR GREATER, INITIAL UPPER-CASE LETTERS SHALL BE 6 INCHES IN HEIGHT AND LOWER-CASE LETTERS 4½ INCHES IN HEIGHT.
2. LETTER STYLES FOR STREET NAME AND SUFFIX SHALL BE 6-INCH SERIES 'B' FROM THE *STANDARD ALPHABETS FOR HIGHWAY SIGNS MANUAL*.
3. 9-INCH EXTRUDED BLANKS SHALL BE A MINIMUM 0.08 INCH GAUGE WITH 6063 T5 OR 6063 T6 ALODINE COATED ALUMINUM SUBSTRATE.
5. THE MINIMUM LENGTH SHALL BE 24 INCHES AND THE MAXIMUM LENGTH SHALL BE 48 INCHES.
6. BOTH SIDES OF STREET NAME SIGNS SHALL BE GREEN (PUBLIC) OR BLUE (PRIVATE) *3M HIGH INTENSITY PRISMATIC (HIP)* REFLECTIVE SHEETING.
7. ALL LETTERS AND NUMBERS SHALL BE WHITE *3M HIGH INTENSITY PRISMATIC (HIP)* REFLECTIVE SHEETING.
8. MOUNTING HARDWARE: SEE DRAWING 523.



Public Works Standard Drawings

**STREET NAME SIGN WITH 6-INCH LETTERING  
FOR 30 MPH TO 40 MPH SPEED LIMITS**

SCALE	NTS	
DATE	JAN '23	REV.
ENGR.	DW	DRAWN KAE
DRAWING NO.	522	